




## Consort



A high performance LED downlight designed for retail applications where glare control is a desirable attribute.

This unit is based upon interchangeable topology allowing future serviceability after the end of life point. (L70)

With 45 degree anti-glare optical recessed finish or 70 degree diffused primary outputs, these units are powered by proven Tridonic drivers and use Citizen LED devices as the fundamental components to ensure a long and reliable service life.





## Features:

- Tridonic Talex driver
- Deep recess light source for low glare
- Multiple dimming options available
- Multiple reflector colour options
- Ideal metal halide replacement option

## Specifications:

- Voltage Input: 220-240VAC
- Power Factor: 0.92
- Beam Angle: 70°
- CCT: 4000K
- CRI: >83
- Operating Temp: -20° to 40°C
- Reflector colour: White
- Dimmable: No
- Warranty: 5 Years

## Options:

Items are special order. Please contact Lumitex for more information.

- CCT Options:
  - 3000K
- Beam angle options:
  - 45° glare control
- Dimmable options:
  - Phase control, 1-10V, Dali
- Secondary reflector colour options:
  - Silver, Black

Part Number	Lumens (Lm)	Watts (W)	Colour (CCT)	Cut-out (mm)	Frame Colour	Beam Angle
LUMRSC31641W	1200	16	4000	150	White	70°
LUMRSC42141W	1800	21	4000	175	White	70°
LUMRSC52841W	2500	28	4000	205	White	70°